

PRIMARY ELEMENT FILTRATION EFFICIENCY*

WSO - WATER	WSO - SMOKE	WSO - OIL
		
<p>Water-soluble coolant: Typically 2-20 microns</p>	<p>Smoke from coolant in hot machining operations: Typically 0.07-1.2 microns</p>	<p>Oil-based coolant: Typically 0.8-5 microns</p>
<p>Water WSO Primary Element Efficiency on 2 microns:</p> <ul style="list-style-type: none"> • 97.5% Draining (98.8% Initial) 	<p>Smoke WSO Primary Element Efficiency on 1.2 microns:</p> <ul style="list-style-type: none"> • 97.7% Draining (99.3% Initial) 	<p>Oil WSO Primary Element Efficiency on 2 microns:</p> <ul style="list-style-type: none"> • 99.3% Draining (99.8% Initial)

* Efficiency test results using aerosolized oil, April 2010.

What's the difference between an 'initial' efficiency and a 'draining' efficiency?

When filters are initially installed, there are many small pore openings between the fibers in the media structure. Those small pores are very effective at capturing droplets. However, as the filter loads with liquid and the droplets coalesce, the small pores fill up with liquid, and all the remaining airflow and small mist droplets must pass through the larger pores in the media. The larger pores are not as efficient at capturing the mist.

- 'Initial' efficiency measurements are taken with a fresh new filter, before the small pores fill up with liquid
- 'Draining' efficiency measurements are taken after the small pores are filled, and the coalesced liquid starts to drain from the filter

The 'Draining' efficiency measurement is more representative of actual performance over the life of the filter.

FINAL FILTER FILTRATION EFFICIENCY

A final filter can provide additional filtration efficiency when desired. There are two optional final filter choices for the WSO:



HEPA FILTER	99.97% efficient* on 0.3 micron mist and smoke
DOP FILTER	95% efficient* on 0.3 micron mist and smoke

* Tested per Mil Standard 282.

SYSTEM – LEVEL EFFICIENCY GUARANTEES

Donaldson Torit can provide written efficiency guarantees based on the application and the selection of primary and final filters.

Please work with your Donaldson Torit representative to obtain a written guarantee.



Significantly improve the performance of your collector with genuine Donaldson Torit replacement filters and parts. **Call Donaldson Torit at 800-365-1331.**

Important Notice

Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.



Donaldson Company, Inc.
Minneapolis, MN
donaldson.com • shop.donaldson.com

North America
Email: donaldson@donaldson.com
Phone: (USA): +1-800-365-1331 • (MX): +1-800-343-36-39

Australasia
Email: marketing.australia@donaldson.com
Phone: +61-2-4350-2000
Toll Free: (AU) +1800-345-837 • (NZ) +0800-743-387

F118172 ENG (02/20) WSO Mist Collectors Efficiency Sheet ©2011-2020 Donaldson Company, Inc.
Donaldson, Torit and the color blue are marks of Donaldson Company, Inc. All other marks belong to their respective owners.

China
Email: info.cn@donaldson.com
Phone: +86-400-820-1038

Donaldson Europe B.V.B.A.
Email: IAF-europe@donaldson.com
Phone: +32-16-38-3811

India
Email: info.difs@donaldson.com
Phone: +91-124-4807-400 • +18001035018

Japan
Email: jp-ndl.jfsweb@donaldson.com
Phone: +81-42-540-4112

Korea
Email: iaf-kr@donaldson.com
Phone: +82-2-517-3333

Latinoamerica
Email: IndustrialAir@donaldson.com
Phone: +52-449-300-2442

South Africa
Email: SAMarketing@donaldson.com
Phone: +27-11-997-6000

Southeast Asia
Email: IAFSEA@donaldson.com
Phone: +65-6311-7373