

TORIT[®] FUME HOOD

Low-Profile Design Flexible Installation Simplified Performance

The Fume Hood's low-profile provides greater installation flexibility than traditional canopy-style hoods and its engineered design provides effective weld fume collection in the most challenging environments. When paired with the optional weld curtains, the Fume Hood can be sized to reduce airflow requirements, ultimately lowering the overall cost of the entire dust collection system. Whether connected to an existing system or a dedicated cartridge collector, the Fume Hood brings added extraction capabilities to any operation.

The Donaldson Torit[®] Fume Hood is the ideal solution for operations that include robotic welding or manual weld cells.

Donaldson

DIMENSIONS & SPECIFICATIONS

Width x Length		Height		Weight	
ft	m	in	mm	lbs	kg
4 x 6	1.2 x 1.8	11	279.4	165	75
6 x 6	1.8 x 1.8	11	279.4	220	99
8 x 8	2.4 x 2.4	11	279.4	320	145
10 x 10	3 x 3	11	279.4	450	203

EQUIPMENT OPTIONS

Weld Curtains

Support Legs

Integrated Lighting

Hanging is the standard installation method.

ADDITIONAL DONALDSON PRODUCTS



Downflo[®] Evolution Cartridge Easy Duct[™] **Dust Collectors**

Spark Cooler®

Extraction Arm

Donaldson's comprehensive dust collection solutions help process owners effectively address their dust, fume, and mist collection challenges by providing knowledgeable guidance, industry-leading equipment as well as unrivaled aftermarket service and support.

Contact your Donaldson representative to learn about the latest weld fume mitigation solutions for your industry.



Donaldson Company, Inc. Minneapolis, MN

donaldsontorit.com • shop.donaldson.com

North America Email: donaldsontorit@donaldson.com Phone: (USA): +1-800-365-1331 • (MX): +1-800-343-36-39

Australia Email: marketing.australia@donaldson.com Phone: +61-02-4350-2033 Toll Free: (AU) +1800-345-837 • (NZ) +0800-743-387 China

Email: info.cn@donaldson.com Phone: +86-400-820-1038 Donaldson Europe B.V.B.A.

Email: IAF-europe@donaldson.com Phone: +32-16-38-3811 India

Email: info.difs@donaldson.com Phone: +91-124-4807-400 • +18001035018

Japan Email: jp-ndl.ifsweb@donaldson.com Phone: +81-42-540-4112

Korea

Email: iaf-kr@donaldson.com Phone: +82-2-517-3333

Latinoamerica Email: IndustrialAir@donaldson.com Phone: +52-449-300-2442

South Africa Email: SAMarketing@donaldson.com Phone: +27-11-997-6000

Southeast Asia Email: IAF.SEA@donaldson.com Phone: +65-6311-7373

IMPORTANT NOTICE: Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.

Brochure No. F119224 ENG (09/23) ©2023 Donaldson Company, Inc. All rights reserved. Donaldson Company, Inc. reserves the right to change or discontinue any model or specification at any time and without notice. Printed in the U.S.A.