

## CLEANLINESS IS CRITICAL

# A small amount of contamination can severely damage engines.

The T.R.A.P. Breather Assembly with huge dirt holding capacity protects the fluids in your storage tanks from airborne particulate contamination and ambient moisture.

It combines a high capacity 3 micron air filter with a deliquescent breather that regenerates itself when air is expelled from the tank. The self-regenerating moisture blocking capability of T.R.A.P. enables extended life and functionality.



### APPLICATIONS

- For use with all diesel fuels and lubricants
- Bulk diesel fuel & oil tanks
- Mobile service trucks
- Indoor and outdoor applications
- High flow and large capacity tanks (may require multiple breather units)

<b>Part Number</b>	<b>P506159</b>
<b>Efficiency</b>	97% efficient @ 3 micron
<b>Max Flow Range</b>	For inlet or outflow up to 500 lpm
<b>Overflow Check Valve</b>	Opens at 2.32 psi / 15 kPa
<b>Operating Temperature</b>	-40 to 93°C
<b>Complete Assembly Dimensions</b>	Height: 366 mm Width: 230 mm
<b>Connection</b>	Brass 1 1/2" BSP
<b>Indicator Port</b>	M10 x 1.0
<b>Replacement Filter</b>	P923075
<b>Alternative Part</b>	P506148
<b>Supersedes</b>	DFF0078

