




Donaldson
FILTRATION SOLUTIONS


ENCLOSURE PROTECTION VENTS

For Automotive Battery Packs



Dual-stage vents help protect automotive battery packs and support battery life and reliability with 4 key functions:

- 1 Sealing and guarding** against water, dirt, contaminants and harsh automotive fluids.
- 2 Continuous pressure equalization** to help protect the battery housing against excess over- or underpressure during the life of the battery.
- 3 Effective ventilation**, allowing damp air which could accumulate inside the battery housing to be expelled with each warming-up cycle, helping to avoid potential internal condensation issues under certain atmospheric conditions.
- 4 Helps ensure proper mitigation** in case of a thermal runaway event inside the battery, allowing large amounts of gases to be expelled in a short timeframe.



HOW DOES IT WORK?


Properly designed venting systems provide protection from contaminants along with pressure equalization during normal operating conditions, helping lead to longer-lasting enclosures and battery life cycles. In the rare case of thermal runaway, the venting system must also be capable of providing immediate pressure relief, helping avoid component failure or propagation to additional cells.

1

The first stage of dual-stage battery venting is pressure equalization. A porous ePTFE membrane allows air and other gases to move in and out of the battery pack. Pressure equalization is needed during normal vehicle operation, due to changes in altitude and temperature.


**2**

In the case of rapid pressure and heat buildup, the second stage helps maintain internal enclosure pressures by allowing gases to escape by either bypassing the membrane with the umbrella flex or bursting the membrane.



The Donaldson Difference

Donaldson's proprietary Tetratex® ePTFE membrane is the core technology behind our vents. Tetratex membrane has a unique microporous structure and is comprised of small, randomly connected fibrils that can be used as permeable water barriers for venting enclosures. Donaldson's proprietary oleophobic treatment process also helps the filter media repel oils.



DONALDSON DUAL-STAGE BATTERY VENTS

Features & Benefits



Dual-Stage BURST Battery Vent

Retention Cap with Burst Pins

- Protects membrane from spray
- Assists membrane burst

Tetratex® ePTFE Membrane

- Pressure equalization
- Protection from water and dirt

Body

- Protects membrane from spray
- Lightweight, durable construction


Quarter-Turn Bayonet Attachment

- Easily secured to the battery pack
- Audible click for installation confirmation
- Also available in Screw-Fit interface

O-Ring

- Reliable sealing to battery pack wall

PRODUCT SPECIFICATIONS

	<div>DUAL-STAGE BURST</div> <div></div>	
MINIMUM AIRFLOW (during normal operation)	17.8 liters/hr @ 10 mbar	
RELEASE PRESSURE	< 375 mbar burst	
TYPICAL DEGASSING AIRFLOW	15 liters/sec @ 70 mbar	
INGRESS PROTECTION (IP) GRADE	IP 67, IP 68, IP 69K*	
MEMBRANE	Hydrophobic & Oleophobic Tetratex ePTFE	
INTERFACE OPTIONS	Bayonet: Quarter turn – various enclosure thicknesses	Screw-Fit
DIMENSIONS: DIAMETER	Bayonet: 51 mm	Screw-Fit: 51 mm
HEIGHT (above enclosure)	Bayonet: 14 mm	Screw-Fit: 14 mm

*IP 69K is dependent on vent location/placement on the battery pack

Donaldson is IATF 16949 certified and our focus is on high quality manufacturing, responsive customer service, and tailored solutions that can be easily integrated into our customer's device or application. Our unique, proprietary membrane and oleophobic treatment processes allow us to select the best types of materials to meet your application requirements. Donaldson Company is a leading global provider of filtration products, with sales and manufacturing of venting products in the U.S., Europe and Asia.

Let Donaldson be your partner in problem solving.



Donaldson Company, Inc.
Venting Solutions
PO Box 1299
Minneapolis, MN 55440-1299 U.S.A
[donaldsonventing.com](https://www.donaldsonventing.com)

United States of America
ivs@donaldson.com
952-887-3874
Europe, Middle East & Africa
venting.solutions@donaldson.com
Greater China
info.cn@donaldson.com
+86-21-2313-7080

Japan
jp-ndl.ivs@donaldson.com
+81-42-540-4119
Korea
ivs.korea@donaldson.com
+82-2-517-3333

Brochure No. F118521 ENG (01/24) USA Enclosure Protection Vents for Automotive Battery Packs.
©2024 Donaldson Company, Inc. Donaldson, Tetratex, and the color blue are marks of Donaldson Company, Inc.
All other marks belong to their respective owners. All rights reserved. All other marks belong to their respective owners.

Important Notice: Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.