



ENCLOSURE PROTECTION VENTS FOR LIGHTING

Integrated Venting Solutions



Outdoor lighting enclosures are continually subjected to challenging environmental conditions such as dust, dirt, and temperature, water, and moisture fluctuations. All of these conditions can affect the lifetime and performance of the electronic components. Donaldson's enclosure protection vents are made with our proprietary Tetratex[®] expanded PTFE membranes, and Donaldson's design and filtration material expertise provide you with the most effective venting solution for your lighting application.

TYPICAL APPLICATIONS

- Street & urban
- Outdoor decorative
- Landscape
- Offshore
- Emergency
- Arena & events
- Industrial

FEATURES & BENEFITS

- Made with Donaldson proprietary Tetratex[®] ePTFE membrane
- Venting allows temperature equalization and reduces condensation
- Prevents ingress of dust and dirt
- Repels water, oils, and other liquids
- IP ratings up to IP69K
- Continuous operating temperature: -40°C to 150°C



VENTING PRODUCTS



PRESS-FIT ENCLOSURE PROTECTION VENTS

Donaldson's Press-Fit enclosure protection vents provide protection from dust, dirt, water, oils, and liquids while allowing air to pass in both directions. Comprised of a filtration membrane and a pressure-sensitive adhesive ring for securing the filter to the device, the uniquely designed adhesive vent integrates easily into existing equipment and can be customized to accommodate a variety of applications.



WELD-FIT ENCLOSURE PROTECTION VENTS

Donaldson Weld-Fit enclosure protection vents combine various component solutions into an Integrated Venting Solution that will ensure your application's performance, no matter what the environment. Weld-Fit solutions may include the ePTFE media paired with the correct welding process applied to a configurable plastic housing. Donaldson engineers will work with you to ensure the proper media treatments (e.g. oleophobic, hydrophobic) and the proper welding method to guarantee your integrated venting solution is the perfect one.



SCREW-FIT ENCLOSURE PROTECTION VENTS

Donaldson's Snap-Fit enclosure protection vents provide protection from dust, dirt, water, oils, and liquids while allowing pressure equalization. The durable vent is available in two sizes – standard and low profile – and is easily integrated into existing equipment. Snap-Fit Vents can be used in a variety of automotive applications such as sensors, ECU's, and lighting as well as protective cases, lighting enclosures, appliances and general enclosures. Donaldson vents are the right choice anywhere protective venting is required.



SNAP-FIT ENCLOSURE PROTECTION VENTS

Donaldson's Snap-Fit enclosure protection vents provide protection from dust, dirt, water, oils, and liquids while allowing pressure equalization. The durable vent is available in two sizes – standard and low profile – and is easily integrated into existing equipment. Snap-Fit Vents can be used in a variety of automotive applications such as sensors, ECU's, and lighting as well as protective cases, lighting enclosures, appliances and general enclosures. Donaldson vents are the right choice anywhere protective venting is required.

Donaldson is IATF 16949:2016 certified and our focus is on high quality manufacturing, responsive customer service, and tailored solutions that can be easily integrated into our customer's device or application. Our unique, proprietary membrane and oleophobic treatment processes allow us to select the best types of materials to meet your application requirements.

Donaldson Company is a leading global provider of filtration products, with sales and manufacturing of venting products in the U.S., Europe and Asia. Let Donaldson be your partner in problem-solving.

Important Notice

Many factors beyond the control of Donaldson can affect the use and performance of Donaldson products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.



Donaldson Company, Inc.
Venting Solutions
PO Box 1299
Minneapolis, MN 55440-1299 U.S.A.

donaldsonventing.com

United States of America:
952-887-3874
ivs@donaldson.com

Europe, Middle East, and Africa:
+32 16 38 3710
venting.solutions@donaldson.com

Greater China:
+86 21 2313 7080
Info.CN@Donaldson.com

Japan:
+81 42 540 4119
jp-ndl.ivs@donaldson.com

Korea:
+82 2 517 3333
ivs.korea@donaldson.com